

HIGH POWER

LOW MAINTENANCE

LEADING
SINCE 1969

LEADER

ENERGY TO PERFORM

SOLAR
TUBULAR BATTERY

SOLAR TUBULAR BATTERY
SUNPOWER
AS PER IS 13369 & IEC 61427



*T&C Apply



dun & bradstreet



ISO-14001

ISO-9001

HIGH POWER

Features



Specification

- Solar tubular Battery design as per IS 13369 & IEC 61427
- Designed for deep cyclic Solar Application Available in 12V & 2V Range.
- MNRE approved Product

Deep Cycle

- Consistent back up high charge acceptance due to usage of quality PE separator.
- Special additives for better charge acceptance & Retention.

Extra Reserve

- Excellent Reserve Capacity as per C10
- Low Rate of Self Discharge.

Low Maintenance

- Special alloy grids ensure low gassing and minimum water loss.
- Low internal resistance, seal proof, leak proof
- Float indicators for Electrolyte level
- Factory Filled and initial Charged, Ready to install.

Environment friendly

- Save fuel and provide eco-friendly environment.
- Special design to make proper use of resources.
- Non-polluting and clean source of energy.



MNRE APPROVED BATTERY



MODEL 12 Volt	AH	TYPE	Packed wt wt ± 3%	L	W	H	Height With float	Charging Current	Battery Layout
LS 2036	20	ST	14.50	260	170	235	255	2	L
LS 4024	40	ST	22.50	410	175	245	280	4	L
LS 4036	40	ST	23.00	410	175	245	280	4	L
LS 6036	60	ST	27.00	505	220	245	310	6	L
LS 7524	75	ST	34.00	505	220	295	310	7.5	L
LS 7536	75	ST	40.00	410	175	295	310	7.5	L
LS 10036	100	ST	41.00	505	220	295	315	10	L
LS 12036	120	ST	43.00	505	220	295	315	12	L
LS 15036	150	TT	57.00	505	190	410	430	15	L
LS 150024	150	TT	55.00	505	190	410	430	15	L
LS 150036	135	TT	57.00	505	190	410	430	13.5	L
LS 180036	150	TT	58.00	505	190	410	430	15	L
LS 200036	180	TT	62.00	505	190	410	430	18	L
LS 240036	200	TT	63.00	505	190	410	430	20	L
LS 150060	135	TT	57.00	505	190	410	430	13.5	L
LS 180060	150	TT	58.00	505	190	410	430	15	L
LS 240060	200	TT	63.00	505	190	410	430	20	L

PILOT INDUSTRIES LTD.

SS-14, 2nd Floor, Aditya Mega Mall, CBD, Delhi-110032
Ph.:+91-11-40033500, Fax. +91-11-40033555



Take back your old battery to local LEADER dealer for recycle process

AUTHORISED DEALER



SCAN HERE TO VISIT WEBSITE



SALES SUPPORT: 8448124005

CUSTOMER CARE: 9650474040

ALL INDIA TOLLFREE: 18003131272