

LEADING
SINCE 1969

LEADER

ENERGY TO PERFORM

TUBULAR INVERTER BATTERY



TALL TUBULAR BATTERY
XTA-POWER

*T&C Apply



dun & bradstreet



FEATURES



EXTRA BACK UP

1. Excellent reserve capacity for long backup.
2. More current density, Max. AH efficiency.
3. Operating specific gravity 1.250 +/-0.005 at 27°C



LONG LIFE

1. Special tubular positive spines cast at high pressure 100 bar to enhance corrosion life under extreme situation.
2. Span life = 1200 Cycle



DEEP CYCLE

1. Consistent back-up high charge acceptance due to usage of PE separator.
2. Special additives for better charge acceptance & retention.



LOW MAINTENANCE

1. Special Alloy grids ensure low gassing and minimum water loss.
2. 20% Extra electrolyte for less topping & batter thermal Management.
3. Low internal resistance seal & leak proof.
4. Float indicators for electrolyte levels.



INVERTER BATTERIES

S.No	Battery Models	Normal Voltage	Rating	Total Warranty (Months)	Dimensions in mm (±5mm)				Battery Layout	Charging Current	Packed Wt. (kg) ±3
					L	W	H	Height with Float			
SHORT TUBULAR BATTERIES											
1.	LDJST18500	12	180Ah	30+30*	515	270	295	315	L	12	57
2.	LDST16500	12	150Ah	24+24*	505	220	295	315	L	12	43
3.	LDST14500	12	135Ah	24+24*	505	220	295	315	L	10	41
4.	LDST13500	12	110Ah	24+24*	505	220	295	315	L	10	40
TALL TUBULAR BATTERIES											
5.	LDR27000	12	270Ah	60+60*	505	190	410	430	L	15	71
6.	LDR25000	12	250Ah	42+42*	505	190	410	430	L	14	67
7.	LDR23000	12	230Ah	42+42*	505	190	410	430	L	13	63
8.	LDR20000	12	200Ah	36+36*	505	190	410	430	L	12	58
9.	LDR18000	12	180Ah	36+36*	505	190	410	430	L	12	58
10.	LDR16000	12	160Ah	36+36*	505	190	410	430	L	12	56
11.	LDR15000	12	150Ah	30+30*	505	190	410	430	L	12	55

PILOT INDUSTRIES LTD.

SS-14, 2nd Floor, Aditya Mega Mall, CBD, Delhi-110032
Ph.:+91-11-40033500, Fax. +91-11-40033555



Take back your old battery to local LEADER dealer for recycle process

AUTHORISED DEALER



SCAN HERE TO VISIT WEBSITE



SALES SUPPORT: 8448124005

CUSTOMER CARE: 9650474040

ALL INDIA TOLLFREE: 18003131272